









## AF SUPER



**The bed-former AF SUPER** allows to work deeply the soil without changing its own natural structure. The teeth of the back rotor shatter the most superficial clods and move the biggest to the front rotor, which turns in the opposite direction. With AF SUPER machine there is a very good preparation of the soil for the sowing or for the transplanting, a good water drainage with a consequent product uniformity. It is possible to work at the same time with 2 or 3 machines model AF SUPER which are logged in a collapsible frame model AIRONE, complete with wheels.

MOD.						P.T.O			
	cm/in	max./макс. cm/in	cm/in		KW/кВт - HP/ЛС	RPM	HP/ЛС	Kg/lb	cm/in
AF SUPER 140	120 • 135 / 47,2 • 53,1	max 25/9,8	140 • 160 / 55,1 • 63	trasmissione a catena chain transmission transmision de cadena transmission a chaîne Ketteantrieb цепью	80,9 - 110	540	55-56	700 / 1543,2	A: 205 B: 160 • 180 • 210 H: 140 A: 80,7 B: 63 • 70,9 • 82,7 • H: 55,1
AF SUPER 160	140 • 155 / 55,1 • 61	160 • 180 / 63 • 70,9	60-70	800 / 1763,7					
AF SUPER 190	170 • 185 / 66,9 • 72,8	190 • 210 / 74,8 • 55,1	70-80	900 / 1984,2					